

HDD-108-MC - Insert

126 108 010 0001
<https://www.wainelectric.com/hdd-108-mc>



Connection type:Crimp connection, Male/female:Male, Specifications:24B|48B, Number of connector contacts:108, Rated current:10A, Rated voltage:250V, Wire gauge (mm²):0.14-2.5mm², Wire gauge (AWG):26-14 AWG

Technical Data

Series	HDD insert series
Connection type	Crimp connection
Male/female	Male
Specifications	24B 48B
Number of connector contacts	108
Grounding contacts	Yes
Rated current	10A
Rated voltage	250V
Rated pulse voltage	4KV
Class of pollution	3
Parameters when class of pollution is 2	10A 230/400V 4kV 2
Rated voltage as per UL/CSA	600V
Insulation resistance	≥10 ¹⁰ Ω
Working temperature	-40°C...+125°C
Mating cycles	≥500
Inserts material	Polycarbonate
Inserts color	RAL 7032 (light gray)
Flame retardant rating as per UL94	V0
Contact material	Copper alloy
Surface treatment	Silver-plated Gold-plated
Contact resistance	≤3mΩ
Wire gauge (mm²)	0.14-2.5mm²
Wire gauge (AWG)	26-14 AWG

HDD-108-MC - Insert

126 108 010 0001
<https://www.wainelectric.com/hdd-108-mc>



Tightening/testing torque	NA
Stripping length	5mm 6mm 8mm
Standard	DIN EN 60 664 DIN EN 61984