


HK-006.1/12-M(2.5-8mm2) - Insert

128 018 011 0001
<https://www.wainelectric.com/hk-006-1-12-m-2-5-8mm2>



Male/female:Male,Connection type:Axial bolt connection | screw connection,Number of connector contacts:6+12,Rated current:40A|10A,Rated voltage:690V|230V|400V,Wire gauge (mm²):2.5-8mm²|0.2-2.5mm²,Wire gauge (AWG):26-14 AWG

Technical Data

Series	HK insert series
Male/female	Male
Connection type	Axial bolt connection screw connection
Specifications	16B
Number of connector contacts	6+12
Grounding contacts	Yes
Rated current	40A 10A
Rated voltage	690V 230V 400V
Rated pulse voltage	6KV 4KV
Class of pollution	3
Insulation resistance	≥10 ¹² Ω
Working temperature	-40°C...+125°C
Mating cycles	≥500
Inserts material	Polycarbonate
Inserts color	RAL 7032 (light gray)
Flame retardant rating as per UL94	V0
Contact material	Copper alloy
Surface treatment	Silver-plated
Contact resistance	≤1mΩ ≤3mΩ
Wire gauge (mm²)	2.5-8mm² 0.2-2.5mm²
Wire gauge (AWG)	26-14 AWG
Tightening/testing torque	2.5mm²→1.5Nm 4mm²→1.5Nm 6mm²→2Nm 0.2-2.5mm²→0.8Nm

HK-006.1/12-M(2.5-8mm2) - Insert

128 018 011 0001

<https://www.wainelectric.com/hk-006-1-12-m-2-5-8mm2>



Stripping length	2.5mm ² →5mm ⁺¹ 4mm ² →5mm ⁺¹ 6mm ² →8mm ⁺¹ 0.2- 2.5mm ² →7.5mm
Standard	DIN EN 60664 DIN EN 61984